



product data sheet

VARCOOL 4795

A multi-functional, high performance heavy duty chlorine and formaldehyde free, water soluble metalworking fluid

VARCOOL 4795 is the latest addition to Varol's very successful range of high performance long-life coolants. The product incorporates the latest combination of HP ester technology with excellent lubricity characteristics to provide both good tool life and surface finish.

VARCOOL 4795 has been developed for use in very soft to hard water and is inherently low foaming at high pressures. The product offers unrivalled cutting performance on a wide range of materials and is fully protected against aluminium staining, making it ideal for machining aerospace alloys as well as titanium and steel in general or arduous machining applications.

VARCOOL 4795 is a formaldehyde free formulation and therefore has excellent operator acceptance and overcomes concerns related to the regulations concerning formaldehyde release biocides. Although not using formaldehyde Varcool 4795 does contain fungicides and special neutralised bio-stable amines, these are important to give the product the stability and sump-life performance required to contain overall fluid costs.

Applications

Reaming	Tapping and threading
Deep hole drilling and boring	Sawing
Milling	Heavy duty turning
Broaching	Metal forming

Features & Benefits

Contains high level of HP synthetic esters	Excellent lubricity characteristics
Formaldehyde and chlorine free	Low foam at high pressures
High performance in arduous operations	High performance in very soft water
Suitable on steel, titanium and aluminium alloys	
Excellent metal forming capabilities	

product data sheet

Typical Operations

Drilling & boring	5% to 8%	General machining	5% to 8%
Reaming	8% to 12%	Boring	8% to 12%
Threading, tapping	7% to 10%	Metal forming	5% to 12%
Broaching, sawing	8% to 10%	Turning, milling	5% to 6%

VARCOOL 4795 Typical Characteristics

Characteristic	Typical Data	Characteristic	Typical Data
Appearance	Amber liquid	Emulsion Appearance	Milky Translucent
PH (@ 5% concentration)	9.3	IP287 corrosion breakpoint	2%
Odour	Characteristic	Refractometer conversion factor	1.40

Additional Technical Information

VARCOOL 4795 is a truly versatile water soluble metalworking fluid that can be used across a diverse range of metals, applications and water hardnesses. The performance parameters of VARCOOL 4795 make it an ideal candidate product to be used throughout a machine shop as a high performance general purpose coolant and grinding fluid. If further information is required please consult your local selling agent or Varol Technical Department for further information

VARCOOL 4795 is free of boron; boric acid has been given the status of a SVHC (substance of very high concern). Boric acid derivatives are used in a number of water-mix metal working fluids. Although there has been a lot of work to prove that the boric acid derivatives do not contain free boric acid there has been a move in the market to move away from boric acid derivatives in water-mix metal working fluids.

Bio-stability - these products give excellent bio-control maintaining bacteria levels well within the HSE (Health and Safety Executive) guidelines.

Corrosion inhibition - These products give equivalent corrosion protection, or better than boron containing products.

For maximum service life, coolant systems should be cleaned and sterilised by treatment with

Varclean System Cleaner. This high performance system cleaner can be used whilst production is continued for up to 24 hours prior to exchange of fluids. Please refer to the **Varclean System Cleaner** data sheet for detailed application information or contact your Varol sales agent.

product data sheet

Varol Metalworking		Varol Machine Lubricants	
Varcut	Neat cutting oils, high performance, extensive range of viscosities	Varlube S Viscosity 32 - 320	Slideway
Varform	Comprehensive range of neat forming oils, including water extendable versions and vanishing oils	Varmulti Viscosity 32 - 680	Multilube - Slideway, Gear, Hydraulic
Varclean	Aqueous based wash fluids, surface cleaners and solvent degreasers	Vargear Viscosity 68 - 460	Industrial Gear
Varcool & Vargrind	Comprehensive range of high performance water soluble fluids. Low, medium, high oil content and synthetics	Varpress Viscosity 5 - 150	Hydraulic oil range covering zinc containing, zinc free and high VI

Operational Recommendations

VARCOOL 4795 is designed to be mixed with water; it has been developed to exhibit full multi-metal compatibility and is suitable for use in soft and hard water types.

Mix emulsions of **VARCOOL 4795** with water by adding concentrate to water and then mixing or use a suitable proportioning mixer unit, these are available on request. The use of an airline to mix the solution is not recommended. Machine top up may require a weaker dilution than the initial machine charge concentration. Recommended concentrations can vary depending on operations, materials, tooling, coolant pressure, coolant flow. The above information is given for guidance. Please contact your representative for further advice.

VARCOOL 4795 should always be stored indoors and protected from frost. Good standards of hygiene and housekeeping should always be adopted when using any metalworking fluid. A separate SDS is available for this product.

As with all modern cutting fluids, concentration control is of paramount importance, therefore regular check by use of a refractometer is recommended for this product. It should be noted that the individual product refractometer correction factor should always be used to ensure accuracy.